

SAFE A LIFE

Never Enter an Unprotected Trench!



WORK SMART!
WORK SAFE!

For your safety:

- ✓ Shore or shield trench walls or slope or bench trench walls.
- ✓ An excavation that has a depth of 4 feet or more must have a safe means for entering and exiting such as the use of ladders, ramps or stairways within 25 feet of workers.
- ✓ Keep heavy equipment at least 2 feet away from trench edges.
- ✓ Know where underground utilities are prior to digging.
Call 811
- ✓ Keep excavated soil or other materials at least 2 feet back from the edge of the trench.
- ✓ Inspect work area for hazards before entering trench and on a continuous basis.



The Members remain responsible for their own operations, safety practices and procedures and should consult with legal counsel as they deem appropriate.

The information we provide is not intended to include all possible safety measures and controls. In addition, the safety information we provide does not relieve the Members of its own duties and obligations with regard to safety concerns, nor does Oregon Home Builders Association guarantee to the Members or others that the Member's property, job sites and/or operations are safe, healthful, or in compliance with applicable laws, regulations or standards.

SAFETY PAGE MEETING GUIDE

Topic: Trench Safety

Employer: _____ Project: _____

Date: _____ Time: _____ Shift: _____

Number in crew: _____ Number attending: _____

Safety or Health issues discussed. Include recent accident investigations and hazards involving tools, equipment, the work environment, work practices and any Safety or Health recommendations:

Follow up on recommendations from last safety meeting:

Record of those attending:

Name: (please print)	Signature:	Company:
1.		
2.		
3.		
4.		
5.		
6.		
7.		
8.		
9.		
10.		
11.		
12.		

Supervisor's remarks:

Supervisor: _____

(Print)

(Signature)